LBA T10

BIDIRECTIONAL SINGLE PEDESTRIAN TURNSTILE

SECURES PEDESTRIAN ACCESS



Intensive operation, up to 20 passages per minute

Can be used as an entrance, exit, or entrance/exit

Access control components integrated into the electronic circuit board on the front panel for easy maintenance

Supplied assembled and wired, with (optional) drilling template

STANDARD CHARACTERISTICS

- **Continuous and intensive operation:** Up to 20 passages per minute
- **Passage:** 1 two-way passage corridor
- **Access panel and access control elements:** Door with 3 locks
- **Passage indicator light:** Smart red/green access indicator light on either side, controlled by the access control system
- **Roof:** Aluminium with a rainwater drainage system
- **Steel plate:** Galvanised steel, polyester paint, RAL 9010
- **Rotor:** Direct connection requiring no fasteners
- **Rotation sensor:** For precise identification of the position out of 360°
- **lighting:** LEDs integrated on either side
- **PLC**: with communication via IP



PAID PARKING FACTORIES OFFICES

LBA T10

TECHNICAL SPECIFICATION

Power supply	230 V
Rotor	40 mm diameter galvanised steel arm
Tubes	ø 40 mm
Paint	Galvanisation + aluminium roof RAL 9010
Weight	350 kg
Opening width	3x120°
Overall dimensions (LxHxD)	1499 x 2328 x 1566 mm
Overall dimensions (LxHxD)	1800 x 1700 x 200 mm
Clearance height	1988 mm
Clearance width	601 mm
IP rating	54

OPTIONS

Customisation

• Polyester paint with a choice of colours (RAL to be defi ned)

• Twilight switch

Visual signals

• Smart LED pictograms for trafficdirection

Safety

• Drilling template

• Two-way locking or locked in one way and free the other way

• Anti-climb roof

• Anti-bacterial bars

• Lockout door

• Firefighterkeyrelease

• Passage reducer

• Stainless steel rotor

• Comfort sleeves

• Heel protector

INSTALLATION



Power supply:

• U-1000 RO 2V 3 x 2.5 mm² cable, 230 V single-phase

Remote control:

• 5-pair 9/10 core telephone cable

Ducts:

• ø40 mm ducts for power and remote control cables

Concrete block:

• 1800 mm long x 1700 mm wide x 200 mm deep

Installation aid:

Drilling template supplied for installation on a concrete block. Two-part pre-assembled set:

• Turnstile assembly

• Roof assembly to be mounted on the access assembly to finalise the installation

LA BARRIÈRE AUTOMATIQUE

For more information, contact our teams on **+33 (0)4 78 86 02 86** or at **contact@onlylba.com** or go to **www.grouplba.com**

DATE OF UPDATED: 12/03/2026